

PROJECT: TER-395-24.50	DRILLING FIRM / OPERATOR: ODOT / A.	DRILL RIG: ACME DRILL RIG	STATION / OFFSET: 164+92:9.0
TYPE: LANDSLIDE	SAMPLING FIRM / LOGGER: ODOT / B.	HAMMER: ACME HAMMER	ALIGNMENT: CL SR 395
PID: 99999 BR ID: N/A	DRILLING METHOD: 3.25" HSA / NQ2	CALIBRATION DATE: 2/20/07	ELEVATION: 585.3 (MSL)
START: 12/9/08 END: 12/10/08	SAMPLING METHOD: SPT / NQ2	ENERGY RATIO (%): 81.9	COORD: 6445586.000 N, 2055511.000 E
			EXPLORATION ID: B-002
			PAGE: 1 of 1

MATERIAL DESCRIPTION AND NOTES	ELEV.	DEPTHS	SPT/RQD	N60	REC (%)	SAMPLE ID	HP (tsf)	GRADATION (%)					ATTERBERG			WC	ODOT CLASS (GI)	BACK FILL
								GR	CS	FS	SI	CL	LL	PL	PI			
ASPHALT (18") OVER CONCRETE (9")		0																
		1																
		2																
	583.1																	
MEDIUM DENSE, BROWN, GRAVEL, "AND" TO SOME SAND, TRACE SILT, TRACE CLAY, MOIST		4																
		3																
		5	5	14	78	SS-1	-	53	20	16	7	4	NP	NP	NP	10	A-1-a (0)	
		4	5															
		7	5	15	89	SS-2	-	51	21	13	8	7	NP	NP	NP	10	A-1-a (0)	
		5																
	579.8																	
STIFF TO VERY STIFF, REDDISH BROWN, SILTY CLAY, SOME GRAVEL, LITTLE SAND, MOIST		2																
		6																
		3	3	8	89	SS-3	1.25	35	6	7	19	33	39	17	22	21	A-6b (8)	
		7	3															
		4	3	11	72	SS-4	1.5	32	9	8	18	33	39	18	21	20	A-6b (7)	
		8																
		4	2															
		9																
		5	2	16	89	SS-5	1.75	-	-	-	-	-	-	-	-	-	18	A-6b (V)
		10																
		7	5															
		7	5	20	72	SS-6	2.25	-	-	-	-	-	-	-	-	-	19	A-6b (V)
		11																
		8																
	573.3																	
SS-7 PUSHING COBBLE LAST 6"		12	5															
		7	5	45	78	SS-7	4.0	24	6	14	25	31	36	19	17	18	A-6b (7)	
		13																
		26																
NONE																		
ABANDONMENT METHODS, MATERIALS, QUANTITIES: PUMPED 20 LB. BENTONITE POWDER; 4 BAGS CEMENT; 25 GAL. WATER																		